



Bulletin 04 / 2026

zur Rahmen-Ausschreibung der ADAC Ravenol Nürburgring Langstrecken-Serie 2026

DMSB-Reg.-Nr. 970/26 genehmigt am 16.02.2026

(Änderungen / Ergänzungen sind *kursiv* geschrieben)

to the Standard Regulations of the ADAC Ravenol Nürburgring Langstrecken-Serie 2026

DMSB-Visa-No. 970/26 approved on 16.02.2026

(Changes / Additions are printed in *italics*)

Only the German and DMSB approved text of the bulletin will be binding.

Teil 2 Technisches Reglement

„Art. 1.14 Referenzfläche Fahrzeughöhe

Sofern durch das Technische Reglement der jeweiligen Klassen und Cups der RAVENOL Nürburgring Langstrecken-Serie keine abweichenden Bestimmungen getroffen werden, ist für alle Fahrzeuge zur Ermittlung der Fahrhöhe ausschließlich die als Referenzfläche ausgewiesene und entsprechend markierte Fläche hinter der Waage im TÜV Rheinland Abnahmegebäude (Service Center) heranzuziehen.

Diese Fläche gilt als verbindliche Referenzebene. Messungen der Fahrhöhe dürfen ausschließlich auf dieser Fläche durchgeführt werden.“

Part 2 Technical Regulations

“Article 1.14 Reference plane for vehicle height

Unless otherwise specified by the Technical Regulations of the respective classes and cups of the RAVENOL Nürburgring Endurance Series, the designated and marked area located behind the weighing scales in the TÜV Rheinland scrutineering building (Service Center) shall be used as the sole reference surface for the determination of the vehicle ride height.

This area shall be considered the mandatory reference plane. Ride height measurements may only be carried out on this surface.”


Anlage 2.6 Techn. Best. BMW M2 Racing Cup | **App. 2.6 Technical Regulations VLN class BMW M2 Racing Cup**

Art. 2.16 Bodenfreiheit | **Article 2.16 Ride Height**

“

Front ride height*			
Left		Right	
113 mm	95mm	113 mm	95mm

*) Refers to setup wheels.




“ ...


Rear ride height*	
Left	Right
133 mm	133 mm

*) Refers to setup wheels with 2.0 bar tire pressure.

Front measuring points on the front axle carrier



Rear measuring points on the rear axle carrier (yellow area)



NOTICE

Alternatively, these measuring points could be determined by a race series organizer. Minimum ride heights and measuring methods are defined by the respective racing series regulations and must be respected at any times!

Der Reifendruck darf für die Messung auf den Referenzdruck (2,0 bar) angehoben werden. Zur Messung der Bodenfreiheit ist der zum Zeitpunkt der Überprüfung montierte Reifen zu verwenden. Sollte einer oder mehrere Reifen auf Grund einer Beschädigung den Luftdruck nicht halten können dürfen der oder die betroffenen Reifen durch neue Reifen ersetzt werden.

Die Bodenfreiheit muss zu jedem Zeitpunkt während einer Veranstaltung mindestens VA: 95 mm und HA: 133 mm betragen.

Die Einhaltung der vorgeschriebenen Bodenfreiheit ist dadurch nachzuweisen, dass der entsprechende Prüfkörper an den definierten Messpunkten unter dem Fahrzeug hindurchgeführt wird. Dabei darf kein Kontakt zwischen Prüfkörper und Fahrzeugbauteilen bestehen.

Der Technische Kommissar ist berechtigt, bei festgestellter erheblicher Abnutzung die am Messpunkt der Vorderachse befindliche Schraube durch eine neue Schraube ersetzen zu lassen.

Die Überprüfung erfolgt auf der ausgewiesenen Referenzfläche des Veranstalters.“

The tyre pressure may be increased to the reference pressure (2.0 bar) for measurement.

The tyre fitted at the time of inspection shall be used to measure ground clearance.

If one or more tyres are unable to maintain air pressure due to damage, the affected tyre(s) may be replaced with new tyres.

The ground clearance must be at least 95 mm at the front axle (VA) and 133 mm at the rear axle (HA) at all times during an event.

Compliance with the prescribed ground clearance shall be demonstrated by passing the designated measuring gauge beneath the vehicle at the specified measurement points. No contact between the gauge and any part of the vehicle is permitted.

The Technical Scrutineer reserves the right to require the replacement of the screw located at the front axle measuring point in cases of significant wear.

The inspection will take place on the designated reference area of the organizer.“

genehmigt / approved 09. April 2026 um / at 15:00 Uhr / o'clock



Nürburgring Langstrecken-Serie
VLN

Christian VORMANN
VLN Leiter Sport / Renndirektor
VLN Head of Sports / Race Director

DMSB genehmigt / approved 09.04.2026

Jana Haböck
Sportreferentin